

bluecool
● ● ● WATER DISPENSERS

U1



An ultra-modern

The u1 epitomises cutting-edge design and innovation with its contoured tap and compact under-counter unit. This is our most discreet range and will fit into any environment seamlessly.



Power requirements

Hertz 50/Volts 220-240

Max power consumption

Chilled & Ambient 80W

Chilled, Ambient & Sparkling 100W

Chilled temperature

Min 2°C/Max 11°C

Throughput litres per hour

Chilled 22

Dimensions

Under counter

Tap height

Dispense height

WxDxH

230x370x390mm

405mm

250mm

Key Features


- Elegant, minimalistic design
- Discreet, hygienic control panel
- Compact under-counter unit
- Consistent low energy consumption
- Chilled, ambient and sparkling

Available accessories


- Sparkling Refill (CO₂ E290)
- CO₂ Regulator with Gauge
- Small Driptray
- Large Driptray
- Waste Kit with Level Sensor
- Sanitisation Kit
- Install Kit with Filter




Water options



Chilled




Ambient




Sparkling

Configuration



Undercounter


Recommended environment



Offices




Hospitality



Leisure


Number of users



1–5



6–10




11–25

u1 Models

Direct Chill, Complete Undercounter System, Chilled, Ambient—601151

Direct Chill, Complete Undercounter System, Chilled, Ambient, Sparkling—601152

Water system



Direct Chill

Direct Chill system utilises innovative technology to chill water instantly. We recommend this system for more demanding environments because of its optimum dispense performance and unrivalled hygienic qualities. Superior to the gravity fed Reservoir system, Direct Chill technology chills water on demand for the ultimate drinking experience.

Phone

+353 (42) 935 2737

Email

info@bluecoolwater.ie

www.bluecoolwater.ie

Distributed by

Ref: 838141

Version: 06052015